



MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO	QAD125H				
MATERIAL	HOUSING-ABS				
	LENS-PC				
COLOR OF LENS	RED(), AMBER(), GREEN(), BLUE()				
FLASHES. PER MIN	60 ~ 80				
USE VOLT.	LED	CURRNET	DC12V~24V	0.5W	MAX.2.150A
			AC110V~220V		MAX.0.320A
VOLUME	MAX. 100dB at 1m				
PROTECTION GRADE	WATER & DUST PROOF IP65				
CABLE ENTRY	$\phi 10$ LEAD HOLE				
COLOR OF HOUSING	MAKER STANDARD				
ACTION	LED STEADY / FLASHING LIGHT				

	ISO2768-1 : CLASS OF TOLERANCE					SURFACE FINISH
	f	m	(C)	v		
FOR LINEAR DIMENSIONS	0.5~3	± 0.05	± 0.1	± 0.2	-	
	3~6			± 0.3	± 0.5	
	6~30	± 0.1	± 0.2	± 0.5	± 1	
	30~120	± 0.15	± 0.3	± 0.8	± 1.5	
	120~400	± 0.2	± 0.5	± 1.2	± 2.5	
400~1000	± 0.3	± 0.8	± 2	± 4		
FOR ANGULAR DIMENSIONS	0~10	$\pm 1^\circ$	$\pm 1^\circ 30'$	$\pm 3^\circ$		
	10~50	$\pm 0^\circ 30'$	$\pm 1^\circ$	$\pm 2^\circ$		
	50~120	$\pm 0^\circ 20'$	$\pm 0^\circ 30'$	$\pm 1^\circ$		
	120~400	$\pm 0^\circ 10'$	$\pm 0^\circ 13'$	$\pm 0^\circ 30'$		

Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
S.H.KIM	J.H.PARK		J.K.HAN	3	2019.03.20
TITLE			MODEL		
QAD125H OUTLINE DRAWING			QAD125H		
			DWG. NO.		
			QAD125H_OUT		
SCALE	SIZE	REV	SHEET		
N/S	A4	00	1/1		