



MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO		QAD100BZ			
MATERIAL		HOUSING-ABS			
		LENS-PC			
		-			
COLOR OF LENS		RED(), AMBER(), GREEN(), BLUE()			
FLASHES. PER MIN		60 ~ 80			
USE VOLT.	LED	CURRNET	DC12V	0.5W	0.460A
			DC24V		0.290A
			AC110V~220V		MAX.0.145A
VOLUME		MAX. 105dB at 1m			
PROTECTION GRADE		WATER & DUST PROOF IP65			
CABLE ENTRY		φ10 LEAD HOLE			
COLOR OF HOUSING		MAKER STANDARD			
ACTION		LED STEADY / FLASHING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE					SURFACE FINISH	-		1		-	
FOR LINEAR DIMENSIONS	f	m	Ⓢ	v		Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QTY
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2019.03.20
	3~6			±0.3	±0.5						
	6~30	±0.1	±0.2	±0.5	±1						
	30~120	±0.15	±0.3	±0.8	±1.5						
	120~400	±0.2	±0.5	±1.2	±2.5						
400~1000	±0.3	±0.8	±2	±4							
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°	TITLE QAD100BZ OUTLINE DRAWING 					
	10~50	±0°30'		±1°	±2°						
	50~120	±0°20'		±0°30'	±1°						
	120~400	±0°10'		±0°13'	±0°30'						
					MODEL		QAD100BZ				
					DWG. NO.		QAD100BZ_OUT				
					SCALE	SIZE	REV	SHEET			
					N/S	A4	00	1/1			