



MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO		QAD100H			
MATERIAL		HOUSING-ABS			
		LENS-PC			
		-			
COLOR OF LENS		RED( ), AMBER( ), GREEN( ), BLUE( )			
FLASHES. PER MIN		60 ~ 80			
USE VOLT.	LED	CURRNET	DC12V~24V	0.5W	MAX.1.020A
			AC110V~220V		MAX.0.210A
VOLUME		MAX. 100dB at 1m			
PROTECTION GRADE		WATER & DUST PROOF IP65			
CABLE ENTRY		$\phi 10$ LEAD HOLE			
COLOR OF HOUSING		MAKER STANDARD			
ACTION		LED STEADY / FLASHING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE					SURFACE FINISH	-		1		-	
FOR LINEAR DIMENSIONS		f	m	(C)		v	Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY
	0.5~3	$\pm 0.05$	$\pm 0.1$	$\pm 0.2$	-	DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	3~6			$\pm 0.3$	$\pm 0.5$	S.H.KIM	J.H.PARK		J.K.HAN	3	2019.03.20
	6~30	$\pm 0.1$	$\pm 0.2$	$\pm 0.5$	$\pm 1$	TITLE QAD100H OUTLINE DRAWING					
	30~120	$\pm 0.15$	$\pm 0.3$	$\pm 0.8$	$\pm 1.5$	MODEL QAD100H					
	120~400	$\pm 0.2$	$\pm 0.5$	$\pm 1.2$	$\pm 2.5$	DWG. NO. QAD100H_OUT					
400~1000	$\pm 0.3$	$\pm 0.8$	$\pm 2$	$\pm 4$	SCALE N/S		SIZE A4	REV 00	SHEET 1/1		
FOR ANGULAR DIMENSIONS	0~10	$\pm 1^\circ$	$\pm 1^\circ 30'$	$\pm 3^\circ$							
	10~50	$\pm 0^\circ 30'$	$\pm 1^\circ$	$\pm 2^\circ$							
	50~120	$\pm 0^\circ 20'$	$\pm 0^\circ 30'$	$\pm 1^\circ$							
	120~400	$\pm 0^\circ 10'$	$\pm 0^\circ 13'$	$\pm 0^\circ 30'$							

