



MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO		QAD125BZ			
MATERIAL		HOUSING-ABS			
		LENS-PC			
		-			
COLOR OF LENS		RED( ), AMBER( ), GREEN( ), BLUE( )			
FLASHES. PER MIN		60 ~ 80			
USE VOLT.	LED	CURRNET	DC12V	0.5W	0.460A
			DC24V		0.290A
			AC110V~220V		MAX.0.145A
VOLUME		MAX. 105dB at 1m			
PROTECTION GRADE		WATER & DUST PROOF IP65			
CABLE ENTRY		$\phi 10$ LEAD HOLE			
COLOR OF HOUSING		MAKER STANDARD			
ACTION		LED STEADY / FLASHING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE					SURFACE FINISH						
FOR LINEAR DIMENSIONS		f	m	(C)		v	Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	3~6			±0.3	±0.5	S.H.KIM	J.H.PARK		J.K.HAN	3	2019.03.20
	6~30	±0.1	±0.2	±0.5	±1	TITLE QAD125BZ OUTLINE DRAWING					
	30~120	±0.15	±0.3	±0.8	±1.5	MODEL QAD125BZ					
	120~400	±0.2	±0.5	±1.2	±2.5	DWG. NO. QAD125BZ_OUT					
400~1000	±0.3	±0.8	±2	±4	SCALE N/S SIZE A4 REV 00 SHEET 1/1						
FOR ANGULAR DIMENSIONS				(C)	v						
	0~10	±1°		±1°30'	±3°						
	10~50	±0°30'		±1°	±2°						
	50~120	±0°20'		±0°30'	±1°						
120~400	±0°10'		±0°13'	±0°30'							

