



※ *(410) represents size without protection cage.

MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO		SDS		
MATERIAL		HOUSING-AL		
		LENS-PC		
		PROTECTION CAGE-SUS316L		
COLOR OF LENS		RED(), AMBER(), GREEN(), BLUE()		
FLASHING PER MIN.		60 ~ 80		
USE VOLT.	XENON	CURRENT	DC12V	MAX. 2.933A
			DC24V	MAX. 1.411A
			AC110V	MAX. 0.360A
			AC220V	MAX. 0.220A
PROTECTION GRADE		WATER & DUST PROOF IP66		
CABLE ENTRY		1/2" PF		
COLOR OF HOUSING		MUNSELL NO. 7.5BG 7/2		
ACTION		XENON LAMP STROBE LIGHT		

	ISO2768-1 : CLASS OF TOLERANCE					SURFACE FINISH
	f	m	(C)	v		
FOR LINEAR DIMENSIONS	0.5-3	± 0.05	± 0.1	± 0.2	-	
	3-6			± 0.3	± 0.5	
	6-30	± 0.1	± 0.2	± 0.5	± 1	
	30-120	± 0.15	± 0.3	± 0.8	± 1.5	
	120-400	± 0.2	± 0.5	± 1.2	± 2.5	
	400-1000	± 0.3	± 0.8	± 2	± 4	
FOR ANGULAR DIMENSIONS	0-10	$\pm 1^\circ$	$\pm 1^\circ 30'$	$\pm 3^\circ$		
	10-50	$\pm 0^\circ 30'$	$\pm 1^\circ$	$\pm 2^\circ$		
	50-120	$\pm 0^\circ 20'$	$\pm 0^\circ 30'$	$\pm 1^\circ$		
	120-400	$\pm 0^\circ 10'$	$\pm 0^\circ 13'$	$\pm 0^\circ 30'$		

Nr.	DWG. NO.	TITLE/NAME	MAT'L	QTY	REFERENCE
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30
TITLE			MODEL		
SDS OUTLINE DRAWING			SDS		
			DWG. NO.		
			SDS_OUT		
SCALE	SIZE	REV	SHEET		
N/S	A4	00	1/1		