



MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO		QMCL100		
MATERIAL		HOUSING-ABS		
MATERIAL		LENS-PC		
COLOR OF LENS		7 COLORS		
USE VOLT.	LED	CURRENT	0.2W	0.200A
				0.120A
VOLUME		MAX. 80dB at 1m		
PROTECTION GRADE		WATER & DUST PROOF IP65		
CABLE ENTRY		$\phi 9$ LEAD HOLE		
COLOR OF HOUSING		MAKER STANDARD		
ACTION		LED STEADY/FLASHING LIGHT		

	ISO2768-1 : CLASS OF TOLERANCE					SURFACE FINISH
	f	m	(C)	v		
FOR LINEAR DIMENSIONS	0.5~3	± 0.05	± 0.1	± 0.2	-	
	3~6			± 0.3	± 0.5	
	6~30	± 0.1	± 0.2	± 0.5	± 1	
	30~120	± 0.15	± 0.3	± 0.8	± 1.5	
	120~400	± 0.2	± 0.5	± 1.2	± 2.5	
	400~1000	± 0.3	± 0.8	± 2	± 4	
FOR ANGULAR DIMENSIONS	0~10		$\pm 1^\circ$	$\pm 1^\circ 30'$	$\pm 3^\circ$	
	10~50		$\pm 0^\circ 30'$	$\pm 1^\circ$	$\pm 2^\circ$	
	50~120		$\pm 0^\circ 20'$	$\pm 0^\circ 30'$	$\pm 1^\circ$	
	120~400		$\pm 0^\circ 10'$	$\pm 0^\circ 13'$	$\pm 0^\circ 30'$	

Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
S.H.KIM	J.H.PARK		J.K.HAN	3	2019.03.20
TITLE			MODEL		
QMCL100 OUTLINE DRAWING			QMCL100		
DWG. NO.			QML100_OUT		
SCALE	SIZE	REV	SHEET		
N/S	A4	00	1/1		

